



Declaration of Performance

No P151-2

1. UNIQUE IDENTIFICATION CODE OF THE PRODUCT -TYPE:

W/PET PLUS-SBS/ICOPAL

2. INTENDED USE/ES:

- a. Roof waterproofing
- b. Roof waterproofing subject to reaction to fire

3. MANUFACTURER:

BMI Polska Sp. z o.o.
ul. Wschodnia 26
45 - 449 Opole

4. SYSTEMS AVCP:

System 2+, System 4

5. HARMONIZED STANDARD:

EN 13707:2004+A2:2009

6. NOTIFIED BODY(IES):

Polskie Centrum Badań i Certyfikacji S.A., No. 1434

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

P. Konrad Machuła

At Opole, on 6th February 2023

7. DECLARED PERFORMANCE:

Essential characteristics	Performance		
External fire performance	---	NPD	
Reaction to fire	---	Class E	
Watertightness	method A	Watertight at 10 kPa	
Tensile properties	max tensile strength	longitudinal	450 ± 150 N/50 mm
		transverse	350 ± 150 N/50 mm
	elongation	longitudinal	30 ± 15 %
		transverse	35 ± 15 %
Root resistance	---	NPD	
Resistance to static loading	---	NPD	
Resistance to impact	---	NPD	
Tear resistance	nail shank	longitudinal	250 ± 100 N
		transverse	250 ± 100 N
Joint strength	---	NPD	
Durability	flow resistance at elevated temperature after artificial ageing	115 ± 15 °C	
Pliability	flexibility at low temperature	-10 °C	
Dangerous substances	---	NPD	