

# Declaration of Performance

No P127-3

**1. UNIQUE IDENTIFICATION CODE OF THE PRODUCT -TYPE:**

VILLAS V60 S42H

**2. INTENDED USE/ES:**

- a. Roof waterproofing
- b. Roof waterproofing subject to reaction to fire

**3. MANUFACTURER:**

BMI Polska Sp. z o.o.  
ul. Wschodnia 26  
45 - 449 Opole

**4. SYSTEMS AVCP:**

System 2+, System 3

**5. HARMONIZED STANDARD:**

EN 13707:2004+A2:2009

**6. NOTIFIED BODY(IES):**

Polskie Centrum Badań i Certyfikacji S.A., No. 1434

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

**P. Konrad Machula**

At Opole, on 6th February 2023

**7. DECLARED PERFORMANCE:**

Essential characteristics	Performance		
External fire performance	---	NPD	
Reaction to fire	---	Class E	
Watertightness	method A	Watertight at 10 kPa	
Tensile properties	max tensile strength	longitudinal	400 ± 100 N/50 mm
		transverse	300 ± 100 N/50 mm
	elongation	longitudinal	4 ± 2 %
		transverse	5 ± 2 %
Root resistance	---	NPD	
Resistance to static loading	---	NPD	
Resistance to impact	---	NPD	
Tear resistance	nail shank	NPD	
Joint strength	---	NPD	
Durability	flow resistance at elevated temperature after artificial ageing	110 ± 15 °C	
Pliability	flexibility at low temperature	0 °C	
Dangerous substances	---	NPD	